Ultra-quiet, space saving wall mount opener.

UL certified to lift even the heaviest of residential garage doors. Automatic deadbolt door lock for maximum security.

Model 98032



PRODUCT GUIDE

LiftMaster
POWERED BY myQ

The ultimate garage door opener from LiftMaster® delivers performance, power and style.

Model 98032



Popular features

Reliable
- First and only UL certified residential opener that can lift doors up to 1,100 lbs.
- Intergrated Batery Backup ensures garage access even when the power is out.
- Warranty that includes lifetime motor, 5-year parts, and 1-year battery and accessories.

Ultra-Quiet Operation
- Designed for ultra-quiet and smooth operation, minimizing noise and vibration to ensure comfortable living spaces above and next to the garage.

Safe and Secure
- Automatic Garage Door Lock deadbolts the door every time it closes, ensuring valuables are protected.
- Timer-to-Close automatically closes the door after a user-defined amount of time: 1 min, 5 min, 10 min or custom.
- Security+ 2.0® safeguards garage access by sending a new code to your garage door opener with every click.
- Motion Detector automatically turns on the light.
- The Protector System Auto-Reverses the door if there's an obstruction.

Smart
- Space-saving and sleek design opens up ceiling space.
- Built-in Wi-Fi® and Bluetooth for the easiest way to connect the garage.
- myQ® Remote LED Light provides full garage light coverage.
- myQ Mobile App lets users receive alerts and control the opener from anywhere.

Elevate how you see your garage

Whether your garage is a sanctuary for a high-end vehicle, a precious workshop or extra storage, the sleek design and luxury features of the LiftMaster 98032 help maximize the garage potential, making it the envy of the neighborhood.



Unprecedented Visibility and Control

The myQ app connects you, your family and friends to your home and garage no matter where you are. Experience unprecedented visibility and control to any access event within your home for ultimate covenience, security and peace of mind. Download the free app today.



In the box



837LM
myQ Remote LED Light
Operates automatically with the opener to illuminate the garage. Works with the myQ App.



L993M
3-Button MAX Remote Control
Operates up to 3 garage door openers.



485LM
2 Backup Batteries Included
Integrated Battery Backup keeps the opener working even when the power is out.



841LM
Automatic Garage Door Lock
Deadbolts the garage door automatically every time it closes.



880LMW
Smart Control Panel®
Motion detector activates the Garage Door Opener lights as soon as movement is detected.

Specifications

Motor
Heavy-Duty 24V, automatic thermal protection, permanent lubrication

More Value, Less Parts
- No more Cable Tension Monitor means faster and easier installation

Mechanics
- Steel Chassis and Plastic Cover
- Internal Chain and Sproket Drive Mechanism (65:1 Gear Reduction)
- Auto-Force Adjustment for changing weather and environmental conditions
- DC Wi-Fi logic with built-in Bluetooth and surge suppressor
- Up to 1,100 lbs. lift capacity, depending on door dimensions

Power
24V DC, 60 Hz voltage, 1.5A current rating, UL Listed, 6' power cord (3-prong)

Speed
4" drum: 7.5" per second upward
7.5" per second downward
6" drum: 8.5" per second upward
8.5" per second downward
8" drum: 10.5" per second upward
10.5" per second downward

Lighting
myQ remote LED Light - 1,000 lumens

Dimensions
- Opener head: 24" L x 7.25" W x 8.5" H
- Max. door height: 14 ft.
- Max. door width: 18 ft.
- Headroom clearance required: 3" in. from center of torsion bar
- Max. door weight: 1,100 lbs.

Warranties
Lifetime: Motor
5 Year: Parts
1 Year: Battery and Accessories

Security+ 2.0
Radio controls:
Operating range -22°F degrees to 149°F degrees,
3-Button MAX Remote Control (L993M), Remote Control Code Format: Security+ 2.0, premium remote control; Garage Door Opener Code Format: Security+ 2.0; Anti-burglary coding.

Encrypted controls:
Smart Control Panel (880LMW), Timer-to-Close, Program Remote Controls, Keypads and myQ accessories, Maintenance Alert System, Easy Wi-Fi Setup.
Radio protocol: Dual SP2 and SP3 Radios
Radio Range: SP2

myQ Radio
902-928 MHz 50-Channel FHSS (frequently hopping spread spectrum); Provides 2-way communication from garage door opener and myQ accessories; enables monitoring and control of garage door opener via smartphone or tablet.

HomeLink® compatible (version 4.0 or higher)
May require an external adapter depending on the model and year of vehicle.
Visit HomeLink.com for additional information.

Pallet Shipping Weight
Quantity 18 Units = 882 lbs.

Pallet Size:
48" x 40" x 50"

Carton (1)
Carton: 28" L x 15" W x 10" H
49lbs.
- Garage Door Opener Head (98032)
- Smart Control Panel (880LMW)
- 3-Button MAX Remote Control (L993M)
- Automatic Garage Door Lock (841LM)
- myQ Remote LED Light (837LM)

For purchase and professional install

Visit LiftMaster.com

For partners
Orders: 800.282.6225 | Support: 800.528.6563 | Self service: LiftMasterTraining.com

© 2026 The Chamberlain Group LLC. All Rights Reserved.

LiftMaster, the Liftmaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group LLC. UL® and the UL logo are trademarks of UL LLC. Wi-Fi® is a registered trademark of Wi-Fi Alliance. HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.
LMGDENPG98032 1/26